



CFS QUICK REFERENCE GUIDE

Surface Treatments

CFS-Acrylic Sealer: Clear acrylic sealer for concrete.

CFS-Concrete Densifier: Lithium based densifier to strengthen the surface of concrete.

CFS-Polished Concrete Guard: Microfilm for polished concrete silane/siloxane.

CFS-Floor Restore: Wax concentrate used to protect and rejuvenate epoxy floors.

Repair Materials

CFS-Fast Set Epoxy Crack Filler: Very fast setting, thin viscosity epoxy used for quick turnaround repairs.

CFS-Fast Set Joint Filler: Fast setting polymer two component joint filler.

CFS-Epoxy Cove Mortar: Epoxy/sand mixture for easy application of epoxy cove.

CFS-Epoxy Mortar Kit: Epoxy/sand mix for larger repairs on concrete floors.

CFS-Epoxy Slurry Kit: Epoxy/sand slurry system for filling rough profile surfaces.

Primers:

CFS-Moisture Vapor Barrier: Used if vapor transmission exceeds 3lbs per 1,000 sq.ft.

CFS-Low Viscosity Epoxy Primer: Used as a primer for epoxy flooring systems.

CFS-Clear Prime: Used for priming either epoxy or polyaspartic coatings.

CFS-Oil Stop Primer: Used to treat oil stained areas before applying any coatings.

CFS-Vertical Epoxy Primer: Water based primer used for vertical applications.

Base/Intermediate Coats

CFS- Intermediate Coat: High build coat for receiving flake or sand.

CFS-Clear Epoxy Binder: Used as a clear coat or for receiving flake or sand.

CFS-Clear Metallic Epoxy: Mixed with pigment for metallic epoxy floors.

CFS-1C-Polyaspartic: Self priming (tintable) polyaspartic can be used as solid color or used to receive flake.

Top Coats

CFS-Topcoat: High build epoxy used as a top coat.

CFS-UV Clear Epoxy Top Coat: Clear epoxy with some UV resistance used as an interior topcoat.

CFS-Vertical Epoxy Top Coat: Water based epoxy used for vertical application.

CFS-High Performance Urethane: Urethane topcoat can be applied on most epoxies as UV resistant/scratch resistant top coat.

CFS-EZ Urethane Topcoat: Single component urethane for scratch/UV protection.

CFS-High Wear High Solids Urethane Topcoat: 3 component urethane for ultimate scratch resistance.

CFS-1C Single Component Polyaspartic: 100% UV stable, extremely durable top coat.