



## Clear Metallic Epoxy Safety Data Sheet

SDS Revision Date: 4/21/2023

### 1. Product and Company Identification

Product Name	Clear Metallic Epoxy
Product Codes	Clear Metallic Epoxy
Manufacturer	Concrete Floor Solutions, Inc.
Street Address	6801 Tilghman Street #113
City, State, Zip	Allentown, PA 18106
Information Phone	610-366-0208
Emergency Phone	Chemtrec 800-424-9300
Prepared By	Jason Kehnel
Date Revised	4/21/2023
Chemical Name or Class	Epoxy Mixture

### 2. Hazards Identification

GHS Classification: Serious eye damage/eye irritation category 2A, Skin irritation category 2, Skin sensitizer category 1, Long term hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Aquatic Toxicity



Hazard Statements:

Warning: Causes serious eye irritation.

Warning: Causes skin irritation

Warning: May cause an allergic skin reaction

Toxic to aquatic life with long lasting effects

Precautionary statements:

## Clear Metallic Epoxy / SDS Revision Date: 4/21/2023

P102 Keep out of reach of children.

P103 Read label before use

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

Response:

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

Other non-classifiable potential hazards:

Acute toxicity oral category 4, Germ Cell Mutagenicity category 2, Toxic to Reproduction (fertility) category 2, Toxic to Reproduction (unborn child) category 2, Specific target organ toxicity repeated exposure (skin, central nervous system (CNS) category 2

### HMIS Hazard Classification

Health: 1      Flammability: 1      Reactivity: 0      Personal Protective Equipment: B

### Potential Health Effects

Eyes: May cause irritation but no corneal injury is likely.

Skin: May cause irritation or allergic skin response.

Ingestion: This material has a probable low acute oral toxicity.

Inhalation: No guide for control known, however, exposure to heated vapors can cause irritation to the nose, throat or mucous membranes.

Health hazards (acute and chronic): Epoxy resins can cause sensitization by exposure through contact or high concentration of vapor. Eyes: Injury if unlikely but stain for evidence of corneal injury.

Medical Conditions Generally Aggravated by Exposure: Respiratory ingredients of this product are regulated as carcinogens.

### Carcinogenicity

OSHA: No

NTP: Yes

IARC: Yes

Additional carcinogenicity information: N/A

### 3. Composition/Information on Ingredients

Ingredient	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Modified Diglycidyl Ether of Bisphenol A	25068-38-6	NONE	NONE	NONE	60-100
Alkyl Glycidyl Ether	68609-97-2	NONE	NONE	NONE	10-30
Siloxanes and Silicones, Di-me Reactions products with silica (non-hazardous)	67762-90-7	NONE	NONE	NONE	0.1-1
Siloxanes and Silicones, Di-methyl (non-hazardous)	63148-62-9	NONE	NONE	NONE	0.1-1
Benzyl Alcohol	100-51-6	NONE	NONE	NONE	1-5
Nonyl Phenol	84852-15-3	NONE	NONE	NONE	3-7
Additive	NJTSRN 800963-5023	NONE	NONE	NONE	<0.3
Solvent Naphtha, Petroleum, Heavy Aromatic	64742-94-5	NONE	NONE	NONE	<0.1
Stoddard Solvent	8052-41-3	100 PPM	100 PPM	NONE	<0.1
1-Methoxy-2-Propanol Acetate	108-65-6	50	NONE	NONE	<0.1
*1,2,4-Trimethylbenzene	95-63-6	25	NONE	NONE	<0.1

**SECTION 3 NOTES:** \*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

**Note:** Ingredients listed without percentages, the percentages are considered a trade secret.

### 4. First Aid Measures

Eyes: Flush eyes with water for at least 15 minutes and consult a physician.

Skin: Skin contact will normally cause no more than irritation but wash affected area with soap and water and remove contaminated clothing promptly.

Ingestion: Low in toxicity, induce vomiting only if large amounts of material are ingested, and otherwise do not induce vomiting. In either case consult with a physician.

Inhalation: Remove to fresh air if effects persist and administer oxygen if necessary.

## 5. Fire Fighting Measures

Flammable limits in air (% by volume)	Upper: N/A Lower: N/A
Flash point	200+F
Method used	SETA FLASH
Extinguishing media	Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog
Special fire fighting procedures	Do not enter a confined area without full bunker gear including a positive pressure NIOSH approved self contained breathing apparatus. Cool all fire exposed containers with water.
Unusual fire and explosion hazards	No unusual fire hazards known.

## 6. Release Measures

Steps to be taken in case material is released or spilled - Wear respirator and protective clothing. Shut off the source at the leak. Remove excess with a vacuum truck and rake up the remainder with an absorbent such as clay and place in disposal containers. Flush area with water to remove residue.

## 7. Handling and Storage

Precautions to be taken in handling and storage - Store in a cool dry place. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking or using toilet facilities. Mixed materials contain the hazards of all the components, therefore, read the MSDS of all the components prior to using material. Properly label all containers.

Other precautions - Avoid all skin contact. Avoid breathing vapors generated from the material. Observe conditions of good general hygiene and safe working practices. Contaminated leather articles can not be cleaned and must be discarded if contaminated with this product. Wash all contaminated clothing prior to the reuse thereof.

## 8. Exposure Controls/Personal Protection

Respiratory protection - Use a NIOSH approved respirator as required to prevent over exposure to vapor in accordance with 29 CFR 1910.134. General exhaust is usually sufficient in lieu of a NIOSH respirator.

Ventilation - General exhaust is usually sufficient to control vapors and exposure hazards

Protective gloves - Impervious gloves, neoprene or rubber.

Eye protection - Splash goggles or glasses with side shields.

Other protective clothing or equipment - Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

Work hygienic practices - Observe good general hygienic practices.

See Section 3 for occupational exposure limit values

## 9. Physical and Chemical Properties

Appearance and Odor - Low viscosity liquid - clear/uncolored

Boiling Point or Range - 200+ F

Vapor Density (Air = 1) - N/A

Specific Gravity (H<sub>2</sub>O = 1) - 1.1

Evaporation Rate - N/A

Solubility in Water - Negligible

Odor Threshold - N/A

pH - N/A

Melting Point/Freezing Point - N/A

Vapor Pressure - N/A

Auto Ignition Temperature - N/A

Partition Coefficient: n-octanol/water - N/A

Decomposition Temperature- N/A

## 10. Stability and Reactivity

Stability - stable

Conditions to Avoid (Stability) - avoid excessive heat or open flames

Incompatibility (Material to Avoid) - Can react vigorously with strong oxidizing agents and strong lewis acids or mineral acids

Hazardous Decomposition or By-Products - CO<sub>2</sub>, Aldehydes, acids. Reaction with some curing agents can generate large amounts of heat.

Hazardous Polymerization - will not occur

## 11. Toxicological Information

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD<sub>50</sub> >5000 mg/kg (rat), Dermal LD<sub>50</sub> >6000 mg/kg (rabbit)

Component CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD<sub>50</sub> >10000 mg/kg (rat), Inhalation LD<sub>50</sub> – no microscopic changes

Component CAS# 84852-15-3: Median Lethal Dose Oral: LD<sub>50</sub> 0.58g/kg (rat) moderately toxic. Dermal LD<sub>50</sub> 2.14g/kg (rabbit) slightly toxic. Skin Draize Test, rabbit, 500 mg/m<sup>3</sup> 24hr – corrosive. Eyes Draize test rabbit, 57.00/110 – extremely irritating. Component is a possible risk of impaired fertility.

Component CAS# 100-51-6: Inhalation LC<sub>50</sub> (4hr) >4178 mg/l (rat), Dermal LD<sub>50</sub> 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and

## Clear Metallic Epoxy / SDS Revision Date: 4/21/2023

histopathological changes in the brain, thymus and skeletal muscles. The No observed adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in a two year study with rats and mice.

Component additive NJTSRN 800963-5023: Acute oral toxicity: LD50 rat > 8,000,000 mg/kg; skin irritation rabbit – no skin irritation

Component CAS# 64742-94-5: LD50/LC50: Draize test, rabbit, skin: 500 uL/24H Mild; Inhalation, rat: LC50 = >590 mg/m<sup>3</sup>/4H; Skin, rabbit: LD50 = >2 mL/kg; Epidemiology: Epidemiological studies involving petroleum refinery workers indicate persons with routine exposure to petroleum or one of its constituents may be at an increased risk to the development of benign neoplasms, digestive tract cancer, and skin cancer.

Component CAS# 8052-41-3: Draize test (rabbit) eye: 500 mg/24hr – Moderate. Epidemiology: Studies involving petroleum refinery workers indicate that persons with routine exposure to petroleum based constituents may be at an increased risk to the development of benign neoplasms, digestive tract cancer and skin cancer. LD50 oral >6000 mg/kg (rat). Dermal LD50 >3000 mg/kg (rabbit). Inhalation LC50 = 5500 mg/kg (4 hr) (rat). Component is a moderate skin irritant. Product is an eye irritant.

Component CAS# 108-65-6: Oral LD50 = 8532 mg/kg (rat). Dermal LD% >5000 mg/kg (rabbit). Inhalation LC50 >100 ppm (4hr) (rat) Component is a moderate skin irritant. Product is an eye irritant

Component CAS# 95-63-6: Oral LD50 (rat) = 5000 mg/kg. Inhalation LC50 (rat) -4h = 18000 mg/m<sup>3</sup>.

## 12. Ecological Information

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

Component CAS# 84852-15-3: Ecotoxicity: Daphnia EC50: 0.14-0.44 mg/l, 48 hr. Component is not readily biodegradable, log Pow: 3-4. Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.. Aquatic Toxicity LC50 96 hr, toxicity rating is <0.10 ppm – extremely toxic

Component CAS# 100-51-6: EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD<sub>2</sub> 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (*Lepomis macrochirus*), LC50 (96hr) 460 ml/l Fathead minnow (*Pimephales promelas*), Toxicity to Algae: IC50 (72hr) 700 mg/l

Component CAS# 95-63-6: Toxicity to fish LC50 (fathead minnow) 7.72 mg/l 96 hr. Toxicity to daphnia and other aquatic invertebrates: Immobilization EC50 (water flea) 3.6mg/l 48hr.

### 13. Waste Disposal

Waste Disposal Method: Dispose of material in a waste disposal site in accordance with local, state, and federal law.

### 14. Transport Information

**DOT:** Not Regulated

**IMO/IMDG:** UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, Marine Pollutant

### 15. Regulatory Information

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list,; is on the PA Right to Know List;

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

Component CAS# 67762-90-7: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component CAS# 63148-62-9: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component CAS# 100-51-6: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

Component CAS# 84852-15-3: This component is listed on TSCA, EINECS, ACIS, MITI and Canada DSL lists.

Component additive NJTSRN 800963-5023: on TSCA List. Not a California Prop 65 chemical  
Component CAS# 64742-94-5. Is on the TSCA and Canada DSL lists.

Component CAS# 8052-41-3: Component is on the TSCA and Canada DSL lists. Components are on the Pennsylvania, California, New Jersey Massachusetts and Minnesota right to know lists.

Component CAS# 108-65-6: Listed on TSCA and DSL

Component CAS# 95-63-6: This component is subject to SARA Title III Section 313 reporting. This component is in the TSCA and Canada DSL Lists. This component is on the Massachusetts, Pennsylvania, and New Jersey right to know lists.

### 16. Other Information

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**Clear Metallic Epoxy / SDS Revision Date: 4/21/2023**

N/A = Not Available

See Section 1 for date of preparation



## 1. Product and Company Identification

Product Name	Clear Metallic Epoxy
Product Codes	Clear Metallic Epoxy
Manufacturer	Concrete Floor Solutions, Inc.
Street Address	6801 Tilghman Street #113
City, State, Zip	Allentown, PA 18106
Information Phone	610-366-0208
Emergency Phone	Chemtrec 800-424-9300
Prepared By	Jason Kehnel
Date Revised	4/21/2023
Chemical Name or Class	Polyamine Mixture

## 2. Hazards Identification

GHS Classification: Skin corrosion/irritation category 1, skin sensitizer category 1B, serious eye damage category 1, acute hazard to aquatic environment category 3, chronic hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Corrosion, Aquatic Toxicity



Hazard Statements:

Danger: Causes severe skin burns and eye damage

Warning: May cause an allergic skin reaction

Danger: Causes serious eye damage

Harmful to aquatic life

Toxic to aquatic life with long lasting effects

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P260 Do not breathe dust/fume/gas/mist/vapors/spray P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

## Clear Metallic Epoxy / SDS Revision Date: 4/21/2023

Response;

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P363 Wash contaminated clothing before reuse.

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P321 If skin irritation or burns develop, Call a doctor/physician.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 If in eyes, immediately call a POISON CENTER or doctor/physician.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

### HMIS HAZARD CLASSIFICATION

Health: 2      Flammability: 1      Reactivity: 0      Personal Protective Equipment: G

#### Potential Health Effects

Eyes: will cause burns to the eyes. High vapor concentrations can cause severe irritation to the eyes.

Skin: can cause skin irritation or possible burns to the skin.

Ingestion: liquid can cause severe damage to mucous membranes if swallowed.

Inhalation: high concentrations of vapor can cause irritation to the respiratory tract, nausea, and dizziness.

Health hazards (acute and chronic): prolonged or repeated exposure may cause asthma and skin sensitization or other allergic responses.

Medical conditions generally aggravated by exposure: respiratory conditions or other allergic response.

Carcinogenicity

OSHA: No      NTP: No      IARC: Yes

#### ADDITIONAL CARCINOGENICITY INFORMATION:

No listed ingredients of this product are regulated as carcinogens.

### 3. Composition/Information on Ingredients

## Clear Metallic Epoxy / SDS Revision Date: 4/21/2023

Ingredient	CAS NO	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Benzyl Alcohol	100-51-6	NONE	NONE	NONE	30-60
3-Aminomethyl-3,5,5-Trimethyl Cyclohexane	2855-13-2	NONE	NONE	NONE	30-60
2-Hydroxybenzoic Acid	69-72-7	NONE	NONE	NONE	3-7
Cycloaliphatic Amine Adduct	68609-08-5	NONE	NONE	NONE	10-30

\*INDICATES TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

### 4. First Aid Measures

Eyes: immediately flush with large amounts of water for at least 15 minutes while lifting upper and lower lids. Get immediate medical assistance.

Skin: flush skin with water for at least 15 minutes and remove all contaminated clothing immediately. Get medical attention if reddening or swelling occurs.

Ingestion: do not induce vomiting. Dilute by giving water or milk to drink if the victim is conscious. Get medical assistance immediately.

Inhalation: remove victim to fresh air if effects persist and administer oxygen if necessary.

### 5. Fire Fighting Measures

Flammable limits in air,  
(% by volume)

Upper: not available  
Lower: not available

Flash point:

200+F

Method used:

Seta flash

Extinguishing media:

Foam, alcohol foam, co2, water fog

Special fire fighting procedures:

Toxic fumes will be evolved when this material is involved in a fire. Self-contained breathing apparatus should be available for fire fighting. Cool fire exposed containers with water.

Unusual fire and explosion hazards: None known.

### 6. Release Measures

Avoid contact with material. Wear the appropriate safety equipment. Stop spillage at source, dyke area to prevent spreading. Pump liquid to salvage tank. Take up the remainder with clay or other absorbent and place in disposal containers.

## 7. Handling and Storage

Precautions To Be Taken In Handling And Storage: Avoid all skin contact. Avoid breathing vapors. Reseal partially used containers. Properly label all containers. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Observe conditions of good industrial hygiene and safe working practices.

Other Precautions: Mixed materials contain the hazards of all the components, therefore, read the MSDS of all components to become familiar with all hazards prior to using this product.

## 8. Exposure Controls/Personal Protection

Respiratory protection: NIOSH approved respirator protection required in the absence of proper environmental controls. For emergencies a self-contained breathing apparatus or a full face respirator is recommended.

Ventilation: avoid breathing vapors. Ventilation must be sufficient to control vapors.

Protective gloves: impervious gloves, neoprene or rubber

Eye protection: splash goggles or glasses with side shields.

Other protective clothing or equipment: wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

Work hygienic practices: observe good general hygienic practices.

See section 3 for occupational exposure limit values

## 9. Physical and Chemical Properties

Appearance and odor: amber clear liquid with amine odor

Boiling point or range: 155 to 401 F

Vapor density (air = 1): N/A

Specific gravity (h<sub>2</sub>o = 1): 1.0

Evaporation rate: N/A

Solubility in water: negligible

Odor threshold: N/A

pH: N/A

Melting point/freezing point: N/A

Vapor pressure: N/A

Auto ignition temperature: N/A

Partition coefficient: n-octanol/water: N/A

Decomposition temperature: N/A

## 10. Stability and Reactivity

Stability: stable

Conditions to avoid (stability): avoid excessive heat or open flames

Incompatibility (material to avoid): can react vigorously with strong oxidizing agents and strong lewis acids or mineral acids

Hazardous decomposition or by-products: CO<sub>2</sub>, aldehydes, acids. Reaction with some curing agents can generate large amounts of heat.

Hazardous polymerization: will not occur.

## **11. Toxicological Information**

No data for the product itself.

Component data:

Component Benzyl Alcohol: Inhalation LC<sub>50</sub> (4hr) >4178 mg/l (rat), Dermal LD<sub>50</sub> 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in a two year study with rats and mice.

Component CAS# 2855-13-2: Oral LD<sub>50</sub> rat 1030 mg/kg, Skin irritation – Corrosive category 1C where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days. Eye irritation – Risk of serious damage to eyes. Product Sensitization (Magnusson-Kingman test) guinea pig: may cause sensitization by skin contact. Product Teratogenicity oral rat NOEL (no observed effect level) 250 mg/kg

Component CAS# 69-72-7: Acute Oral Toxicity LD<sub>50</sub> (rat) = 891 mg/kg (behavioral somnolence (general depressed activity, Behavioral muscle weakness)). Acute Inhalation LC<sub>50</sub> (rat) >900 mg/m<sup>3</sup>, 1 hr. Acute Dermal LD<sub>50</sub> (rabbit) >10,000 mg/kg. Skin Irritation (rabbit) – mild skin irritation -24hr. Eye Irritation (rabbit) – severe eye irritation.

## **12. Ecological Information**

No data for the product itself.

Component data:

Component Benzyl Alcohol: EC<sub>50</sub> (48hr) 400 mg/l Daphnia Magna, EC<sub>50</sub> (72hr) 2600 mg/l Algae, Biodegradation BOD<sub>2</sub> 62. Slightly or not bioaccumulative. Toxicity to fish: LC<sub>50</sub> (96 hr) 10 mg/l Bluegill sunfish (*Lepomis macrochirus*), LC<sub>50</sub> (96hr) 460 ml/l Fathead minnow (*Pimephales promelas*), Toxicity to Algae: IC<sub>50</sub> (72hr) 700 mg/l

Component CAS# 2855-13-2: Biodegradability 42% and is not readily biodegradable.

Bioaccumulation: - no significant accumulation of the substance in organisms is to be expected.

Mobility: The soil mobility of the substance is only minimally affected by adsorption to soil components. Toxicity to fish: LC<sub>50</sub> *Leuciscus idus* 110 mg/l (96hr). Toxicity to Daphnia NOEC 3 mg/l (504hr). EC<sub>50</sub> *Daphnia magna* 23 mg/l (48 hr). ErC<sub>50</sub> *scenedesmus subspicatus* 50 mg/l (72 hr). NOEC *scenedesmus subspicatus* 1.5 mg/l (72 hr). Toxicity to bacteria: EC<sub>10</sub>

*Pseudomonas putida* 1120 mg/l (18 hr).

Component CAS# 69-72-7: Toxicity to Fish LC<sub>50</sub> (*Leuciscus idus* – 96 mg/l. Toxicity to *Daphnia magna* – 105 mg/l, 24 hr. Component Mutagenic Effects: Mutagenic for bacteria and/or

yeast. Developmental toxicity: Classified reproductive system toxin/female, development toxin possible.

### **13. Waste Disposal**

Waste Disposal Method: Dispose of material as a hazardous waste according to federal, state, and local regulations.

### **14. Transport Information**

DOT: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE), 8, PG III

IMO/IMDG: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE), 8, PG III,

### **15. Regulatory Information**

No data for the product itself.

Component data:

Component Benzyl Alcohol: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

Component CAS# 2855-13-2: Acute health hazard. Ingredients on TSCA. International Chemical status listed/registered – EINECS/ELINCS, DSL, AICS, MITI, TCOL, PICCS, China, and New Zealand.

Component CAS# 69-72-7: Component is on the Pennsylvania and New Jersey right to know lists. Components are on the TSCA and Canada DSL lists.

Component CAS# 68609-08-5 is on the Canada DSL and TSCA lists.

### **16. Disclaimer**

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

End of Document