



## Vertical Epoxy Top Coat Safety Data Sheet

SDS Revision Date: 5/23/2023

### 1. Product and Company Identification

Product Name	Vertical Epoxy Top Coat
Product Codes	Vertical Epoxy Top Coat
Manufacturer	Concrete Floor Solutions, Inc.
Street Address	6801 Tilghman Street #113
City, State, Zip	Allentown, PA 18106
Information Phone	610-366-0208
Emergency Phone	Chemtrec 800-424-9300
Prepared By	Jason Kehnel
Date Revised	5/23/2023
Chemical Name or Class	Epoxy Mixture

### 2. Hazards Identification

GHS Classification: Serious eye damage/eye irritation category 2A, skin irritation category 2, skin sensitizer category 1, long term hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Aquatic Toxicity



Hazard Statements:

Warning: Causes serious eye irritation.

Warning: Causes skin irritation

Warning: May cause an allergic skin reaction

Toxic to aquatic life with long lasting effects

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P264 Wash hands thoroughly after handling.

## Vertical Epoxy Top Coat / SDS Revision Date: 5/23/2023

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

Response

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

Other Non-classifiable potential hazards

Carcinogen category 2

### HMIS Hazard Classification

Health: 1      Flammability: 1      Reactivity: 0      Personal Protective Equipment: G

### Potential Health Effects

Eyes: May cause irritation but no corneal injury is likely.

Skin: May cause irritation or allergic skin response.

Ingestion: This material has a probable low acute oral toxicity.

Inhalation: No guide for control known, however exposure to heated vapors can cause irritation to the nose, throat, or mucous membranes.

Health hazards (acute and chronic): Epoxy resins can cause sensitization by exposure through contact or high concentration of vapor. Eyes: Injury is unlikely but stain for evidence of corneal injury.

Medical Conditions Generally Aggravated by Exposure: Respiratory conditions or other allergic ailments.

### Carcinogenicity

OSHA: No

NTP: Yes

IARC: Yes

**Additional carcinogenicity information:** Some colors may contain carbon black - Explanation Of Carcinogenicity: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B. IARC has determined that crystalline silica inhaled in the form of quartz is carcinogenic to humans (Group 1- carcinogenic to humans). The NTP classifies respirable crystalline silica as reasonably anticipated to be a carcinogen. Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

### 3. Composition/Information on Ingredients

Ingredient	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Modified Diglycidyl Ether of Bisphenol A	25068-38-6	NONE	NONE	NONE	30-60
Alkyl Glycidyl Ether	68609-97-2	NONE	NONE	NONE	0.1-1
Talc	14807-96-6	20 mg/m3	20 mg/m3	20 mg/m3	10-30
*Crystalline Silica (as a component of Talc)	14808-60-7	0.05 mg/m3	0.025 mg/m3	0.05 mg/m3	0.1-1
Limestone	1317-65-3	15 mg/m3	5 mg/m3	NONE	10-30
*Xylene	1330-20-7	100 PPM	100 PPM	150 PPM	0.1-1
*Ethyl Benzene (as a component of Xylene)	100-41-4	100 PPM	100 PPM	125 PPM	<0.1
Benzyl Alcohol	100-51-6	NONE	NONE	NONE	1-5
Alkyl Quaternary Ammonium Bentonite	68953-58-2	50 mg/m3	10 mg/m3	20 mg/m3	1-5
*Crystalline Silica	14807-60-7	10 mg/m3	.1 mg/m3	.1 mg/m3	0.1-1
Hydrocarbon Resin	Non-Hazardous	NONE	NONE	NONE	3-7
*Naphthalene	91-20-3	10 PPM	10 PPM	NONE	<0.05
Hydroxy Modified Resin	Non-Hazardous	NONE	NONE	NONE	3-7
Colors May Contain @ 10-30%:					
Titanium Dioxide	13463-67-7	10 mg/m3	10 mg/m3	5 mg/m3	
*Carbon	1333-86-4	3.5 PPM	3.4 PPM	NONE	<1
Silicon Dioxide	7631-86-9	6 mg/m3	10 mg/m3	NONE	
Ferric Oxide	1309-37-1	10 mg/m3	8 mg/m3	NONE	
Iron III Hydroxide	20344-49-4	15 mg/m3	5 mg/m3	NONE	
Yellow Pigment	Not Available	NONE	NONE	NONE	
Zinc Sulfide	1314-98-3	NONE	NONE	NONE	
Barium Sulfate	7727-43-7	NONE	NONE	NONE	
Pigment Yellow 65	6528-34-3	NONE	NONE	NONE	

## Vertical Epoxy Top Coat / SDS Revision Date: 5/23/2023

C.I. Pigment Blue	147-14-8	1 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>	NONE	
Aluminum Oxide	1344-28-1	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	NONE	
Iron Oxide Yellow	51274-00-1	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	NONE	

**SECTION 3 NOTES:** \*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372. Xylene ACGIH STEL = 150 PPM.

**Note:** Ingredients listed without percentages, the percentages are considered a trade secret.

### 4. First Aid Measures

Eyes: Flush eyes with water for at least 15 minutes and consult a physician.

Skin: Skin contact will normally cause no more than irritation, but wash affected areas with soap and water and remove contaminated clothing promptly.

Ingestion: Low in toxicity, induce vomiting only if large amounts of material are ingested.

Otherwise do not induce vomiting. In either case, consult a physician.

Inhalation: Remove to fresh air if effects persist and administer oxygen if necessary.

### 5. Fire Fighting Measures

Flammable limits in air Upper: N/A

(% by volume) Lower: N/A

Flash point 200+F

Method used Seta Flash

Extinguishing media Foam, Alcohol Foam, CO<sub>2</sub>, Dry Chemical, Water Fog

Special fire fighting procedures Do not enter a confined area without full bunker gear including a positive pressure NIOSH approved self-contained breathing apparatus. Cool all fire exposed containers with water.

Unusual fire and explosion hazards None known.

### 6. Release Measures

Steps to be taken in case material is released or spilled - wear respirator and protective clothing. Shut off the source at the leak. Remove excess with a vacuum truck and take up the remainder with an absorbent such as clay and place in disposal containers. Flush area with water to remove residue.

### 7. Handling and Storage

Precautions to be taken in handling and storage - store in a cool dry place. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking, or using toilet facilities.

Mixed materials contain the hazards of all the components, therefore, read the MSDS of all the components prior to using this material. Properly label all containers.

Other precautions - Avoid all skin contact. Avoid breathing vapors generated from the material. Observe conditions of good general hygiene and safe working practices. Contaminated leather articles cannot be cleaned and must be discarded if contaminated with this product. Wash all contaminated clothing prior to the reuse thereof.

## **8. Exposure Controls/Personal Protection**

Respiratory protection - NIOSH approved respirator required to prevent overexposure to vapor in accordance with 29 CFR 1910.134. General exhaust is usually sufficient in lieu of a NIOSH respirator.

Ventilation - General exhaust is usually sufficient to control vapors and exposure hazards.

Protective gloves - Impervious gloves, neoprene or rubber.

Eye protection - Splash goggles or glasses with side shields.

Other protective clothing or equipment - Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

Work hygienic practices - Observe good general hygienic practices.

**See Section 3 for occupational exposure limit values**

## **9. Physical and Chemical Properties**

Appearance and Odor - Low viscosity liquid in varying colors

Boiling Point or Range - 200 to 279 F

Vapor Density (Air = 1) - N/A

Specific Gravity (H<sub>2</sub>O = 1) - 1.5

Evaporation Rate - N/A

Solubility in Water - Negligible

Odor Threshold - N/A

pH - N/A

Melting Point/Freezing Point - N/A

Vapor Pressure - N/A

Auto Ignition Temperature - N/A

Partition Coefficient: n-octanol/water - N/A

Decomposition Temperature- N/A

## **10. Stability and Reactivity**

Stability - stable

Conditions to Avoid (Stability) - avoid excessive heat or open flames

## Vertical Epoxy Top Coat / SDS Revision Date: 5/23/2023

Incompatibility (Material to Avoid) - can react vigorously with strong oxidizing agents and strong lewis acids or mineral acids.

Hazardous Decomposition or By-Products - CO<sub>2</sub>, Aldehydes, Acids. Reaction with some curing agents can generate large amounts of heat.

Hazardous Polymerization - will not occur

### 11. Toxicological Information

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

Component CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes

Component Titanium Dioxide: Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

Component CAS# 14807-96-6: Carcinogenic effects – this component may contain crystalline silica dust that can cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen

Component Limestone: LD50 Oral (rat) = 6450 mg/kg. This product contains greater than 0.1% crystalline silica which is listed as a group 1 carcinogen by IARC, a known carcinogen by NTP, OSHA and as A2 suspected human carcinogen by ACGIH

Component Xylene: Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may affect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. Xylene may contain ethyl benzene, and toluene. Ethyl benzene has shown limited evidence of a carcinogenic effect.

Component Iron III hydroxide CAS# 20344-49-4: Acute Oral Toxicity LD50 >5000 mg/kg (rat).

Component Carbon: IARC lists carbon as a possible human carcinogen Category 2B. LD50 – Intravenous, mouse = 440 mg/kg

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.. Acute oral value of 20 gm/kg or greater in rats

Component Benzyl Alcohol: Inhalation LC50 (4hr) >4178 mg/l (rat), Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in a two year study with rats and mice.

## Vertical Epoxy Top Coat / SDS Revision Date: 5/23/2023

Component CAS# 68953-58-2: Carcinogenic effects – this component may contain crystalline silica dust that can cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen. Oral LD50 (rat) > 8g/mg

### 12. Ecological Information

No data for the product itself.

Component data:

CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

Component Titanium Dioxide: Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50

Component CAS# 14807-96-6: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

Component Limestone: inert material

Component Xylene: Acute Toxicity: Fish: Toxic 1 < LCECIC50 < 10 mg/l, Aquatic

Invertebrates: Toxic 1 < LC/EC/IC50 <10 mg/l, Algae: Toxic 1 < LC/EC/IC50 <10 mg/l.

Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidises rapidly by photo-chemical reactions in air.

Component Iron III hydroxide CAS# 20344-49-4: Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Toxicity to Microorganisms EC0 > 10000 mg/l (pseudomonas putida)

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

Component Benzyl Alcohol: EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD<sub>2</sub> 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (Lepomis macrochirus), LC50 (96hr) 460 ml/l Fathead minnow (Pimephales promelas), Toxicity to Algae: IC50 (72hr) 700 mg/l

Component CAS# 68953-58-2: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

### 13. Waste Disposal

Waste Disposal Method: Dispose of material in a waste disposal site in accordance with local, state, and federal law.

### 14. Transport Information

DOT: Not Regulated



## Vertical Epoxy Top Coat / SDS Revision Date: 5/23/2023

**IMO/IMDG:** Un3082, environmentally Hazardous Substances, Liquid, N.O.S. (Contains Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, Marine Pollutant

### 15. Regulatory Information

No data for the product itself.

Component data:

CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list,; is on the PA Right to Know List;

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

Component CAS# 14807-96-6 may contain Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

Component Titanium Dioxide: Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List.

Titanium Dioxide is in inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN).

Component Limestone: TSCA listed. Canada Exempt, naturally occurring Substance. EINECS, ECL, ENCS, CIES, PICCS listed. This product is known to the state of California to cause cancer or reproductive effects.

Component Xylene: Xylene contains EPCRA section 313 chemicals subject to the reporting requirements of the emergency planning and community right to know act of 1968. (Maximum wt % for components of xylene are: M-Xylene CAS# 108-38-3 is 46%, P-Xylene CAS# 106-42-3 is 20%, Ethylbenzene CAS# 100-41-4 is 19%, O-Xylene CAS# 95-47-6 is 16%.. Xylene and its components are on the California Proposition 65 list for developmental toxicity, Reproductive toxicity and carcinogen list. Ingredients are on the TSCA list, DSL Canada, AICS, China, EINECS, ENCS, Korea, New Zealand, Philippines inventory lists and on the Massachusetts, New Jersey, Pennsylvania right to know lists Ethyl Benzene a component of xylene has been designated by IARC as a possible carcinogen to humans based on increased tumor incidence in laboratory animals. risk phrases R10 Flammable R20/21 Harmful by inhalation and in contact with skin, R38 irritating to skin, S25 Avoid contact with eyes.

Component Carbon: Contains Proposition 65 Chemicals .Carbon: is listed on TSCA and DSL Canada

Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on the TSCA list and Canada DSL.

Component CAS# 1309-37-1: Component is on the TSCA list and Canada DSL.

Component Iron III hydroxide CAS# 20344-49-4: Listed on TSCA Inventory. Potential exposure to all of the California proposition 65 chemicals have been determined to be below the No



## Vertical Epoxy Top Coat / SDS Revision Date: 5/23/2023

significant risk level (NSRL). Components are on the Pennsylvania right to know substance list. Component contains the following chemicals listed on the Pennsylvania RTK special hazardous Substance lists: chromium CAS# 7440-47-3 (0.02%) and nickel CAS# 7440-02-0 (0.015%).

Component contains the following ingredients which are on the Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.02%), arsenic CAS# 7440-38-2 (60 ppm), Beryllium CAS# 7440-41-7 (1ppm) and Nickel CAS# 7440-02-0 (0.015%) Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.015%), arsenic CAS# 7440-38-2 (60 ppm), Beryllium CAS# 7440-41-7 (1ppm) and Cobalt CAS# 7440-48-4 (70 ppm)..

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

Component CAS# 147-14-8: Component is on the TSCA List. and not controlled under WHMIS. Component is a CERCLA hazardous substance

Component CAS# 1344-28-1: Component is on the Massachusetts, New Jersey, Pennsylvania right to know lists. Components are on the TSCA list and Canada DSL.

Component CAS# 51274-00-1: Component is on the TSCA list and Canada DSL.

Component Benzyl Alcohol: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

Component CAS# 68953-58-2: may contain Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance. Component is on the DSL, EINECS, AICS, ENCS, ECL, PICCS and CLECS lists

Component HYDROCARBON RESIN: Component contains 0.01-0.06 wt% Naphthalene CAS# 91-20-3 with a CERCLA RQ of 100 pounds. Components are on the TSCA list and Canadian DSL list. Component does not contain any reportable chemicals above the de minimis level for section 313. Components are not hazardous as defined by CFR 1910.1200 or Title III section 312/313 of the superfund amendment. Naphthalene is known to the state of California to cause cancer. Naphthalene is on the Pennsylvania, Massachusetts and New Jersey right to know lists.

Component HYDROXY MODIFIED RESIN.: Component is not hazardous as defined by CFR 1910.1200 and under the provisions of Title III Section 311/312 of the Superfund amendments and Reauthorization Act. Components are on the TSCA list..

### 16. Other Information

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

## 1. Product and Company Identification

Product Name	Vertical Epoxy Top Coat
Product Codes	Vertical Epoxy Top Coat
Manufacturer	Concrete Floor Solutions, Inc.
Street Address	6801 Tilghman Street #113
City, State, Zip	Allentown, PA 18106
Information Phone	610-366-0208
Emergency Phone	Chemtrec 800-424-9300
Prepared By	Jason Kehnel
Date Revised	5/23/2023
Chemical Name or Class	Polyamine Mixture

## 2. Hazards Identification

GHS Classification: Acute oral toxicity category 4, acute dermal toxicity category 4, serious eye irritation/damage category 1, skin sensitizer category 1B, skin corrosion/irritation category 1, reproductive toxicity category 2, acute hazard to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Corrosion, Health Hazard, Aquatic Toxicity



Hazard Statements:

Warning: Harmful if swallowed

Warning: Harmful in contact with skin

Danger: Causes serious eye damage

Warning: May cause an allergic skin reaction

Danger: Causes severe skin burns and eye damage

Warning: Suspected of damaging fertility or the unborn child.

Toxic to aquatic life

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

## Vertical Epoxy Top Coat / SDS Revision Date: 5/23/2023

P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves and clothing to prevent skin contact.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P273 Avoid release to the environment.

Response;

P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: wash with plenty of soap and water

P312 Call a POISON CENTER or doctor/physician if you feel unwell

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 If in eyes, immediately call a POISON CENTER or doctor/physician.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 take off contaminated clothing and wash it before reuse.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

P405 Store locked up

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

### HMIS HAZARD CLASSIFICATION

Health: 2      Flammability: 1      Reactivity: 0      Personal Protective Equipment: G

Potential Health Effects

Eyes: Will cause burns to the eyes. High vapor concentrations can cause severe irritation to the eyes.

Skin: Can cause irritation or possible burns to the skin.

Ingestion: Liquid can cause severe damage to mucous membranes if swallowed.

Inhalation: High concentrations of vapor can cause irritation to the respiratory tract, nausea, and dizziness.

Health hazards (acute and chronic): Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic responses.

Medical conditions generally aggravated by exposure: Respiratory conditions or other allergic ailments.

## Vertical Epoxy Top Coat / SDS Revision Date: 5/23/2023

Carcinogenicity

OSHA: No

NTP: No

IARC: No

### 3. Composition/Information on Ingredients

Ingredient	CAS NO	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
3-Aminomethyl-3,5,5-Trimethyl Cyclohexane	2855-13-2	NONE	NONE	NONE	10-30
Nonyl Phenol	84852-15-3	NONE	NONE	NONE	30-60
Amino Terminated Polyether	9046-10-0	NONE	NONE	NONE	30-60

\*No toxic chemical(s) subject to the reporting requirements of section 313 Title III and of 40 CFR 372 are present.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

### 4. First Aid Measures

Eyes: Flush eyes with water for at least 15 minutes while lifting upper and lower lids. Get immediate medical assistance.

Skin: Flush skin with water for at least 15 minutes and remove all contaminated clothing immediately. Get medical attention if reddening or swelling occurs.

Ingestion: Do not induce vomiting. Dilute by giving water or milk to drink if the victim is conscious. Get medical attention immediately.

Inhalation: Remove victim to fresh air and administer oxygen if necessary.

### 5. Fire Fighting Measures

Flammable limits in air,  
(% by volume)

Upper: not available

Lower: not available

Flash point:

200+F

Method used:

Seta flash

Extinguishing media:

Foam, alcohol foam, co2, water fog

Special fire fighting procedures:

Toxic fumes will be evolved when this material is involved in a fire. A self contained breathing apparatus should be available for firefighting. Cool fire exposed containers with water.

Unusual fire and explosion hazards: None known.

### 6. Release Measures

Steps to be taken in case material is released or spilled: avoid contact with material. wear the appropriate safety equipment. stop spill at source, dyke area to prevent spreading. pump liquid to the salvage tank. take up the remainder with clay or other absorbent and place in disposal containers.

## **7. Handling and Storage**

Precautions to be taken in handling and storage: avoid all skin contact. avoid breathing vapors. reseal partially used containers. properly label all containers. wash with soap and water before eating, drinking, smoking, or using toilet facilities. observe conditions of good industrial hygiene and safe working practices.

Other precautions: mixed materials contain the hazards of all the components, therefore, read the msds of all components to become familiar with all hazards prior to using this product.

## **8. Exposure Controls/Personal Protection**

Respiratory protection: NIOSH approved respirator required in the absence of proper environmental controls. For emergencies a self contained breathing apparatus or a full face respirator is recommended.

Ventilation: Avoid breathing vapors. Ventilation must be sufficient to control vapors.

Protective gloves: impervious gloves, neoprene or rubber

Eye protection: splash goggles or glasses with side shields.

Other protective clothing or equipment: wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

Work hygienic practices: observe good general hygienic practices.

See section 3 for occupational exposure limit values

## **9. Physical and Chemical Properties**

Appearance and odor: Amber clear liquid with amine odor

Boiling point or range: 401 to 560 F

Vapor density (air = 1): N/A

Specific gravity (h<sub>2</sub>o = 1): 1.0

Evaporation rate: N/A

Solubility in water: negligible

Odor threshold: N/A

pH: N/A

Melting point/freezing point: N/A

Vapor pressure: N/A

Auto ignition temperature: N/A

Partition coefficient: n-octanol/water: N/A

Decomposition temperature: N/A

## 10. Stability and Reactivity

Stability: stable

Conditions to avoid (stability): avoid contact with open flames and all sources of ignitions and sparks.

Incompatibility (material to avoid): avoid contact with strong oxidizing agents, mineral acids, and epoxy resins in uncontrolled amounts.

Hazardous decomposition or by-products: co, co2, nox

Hazardous polymerization: will not occur.

## 11. Toxicological Information

No data for the product itself.

Component data:

Component CAS# 2855-13-2: Oral LD50 rat 1030 mg/kg, Skin irritation – Corrosive subcategory 1C where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days. Eye irritation – Risk of serious damage to eyes. Product Sensitization (Magnusson- Kingman test) guinea pig: may cause sensitization by skin contact. Product Teratogenicity oral rat NOEL (no observed effect level) 250 mg/kg

Component Nonyl Phenol: Median Lethal Dose Oral: LD50 0.58g/kg (rat) moderately toxic. Dermal LD50 2.14g/kg (rabbit) slightly toxic. Skin Draize Test, rabbit, : 500 mg/m<sup>3</sup> 24hr – corrosive. Eyes Draize test rabbit, 57.00/110 – extremely irritating. Component is a possible risk of impaired fertility.

Component CAS# 9046-10-0: Oral LD50 (rat) = 2880 mg/kg; Dermal LC50 (rabbit) = 2980 mg/kg. Corrosive to skin of rabbit. Severe eye irritation (rabbit)

## 12. Ecological Information

No data for the product itself.

Component data:

Component CAS# 2855-13-2: Biodegradability 42% and is not readily biodegradable.

Bioaccumulation: - no significant accumulation of the substance in organisms is to be expected.

Mobility: The soil mobility of the substance is only minimally affected by adsorption to soil components. Toxicity to fish: LC50 *Leuciscus idus* 110 mg/l (96hr). Toxicity to *Daphnia* NOEC 3 mg/l (504hr). EC50 *Daphnia magna* 23 mg/l (48 hr). ErC50 *scenedesmus subspicatus* 50 mg/l (72 hr). NOEC *scenedesmus subspicatus* 1.5 mg/l (72 hr). Toxicity to bacteria: EC10 *Pseudomonas putida* 1120 mg/l (18 hr).

Component Nonyl Phenol: Ecotoxicity: *Daphnia* EC50: 0.14-0.44 mg/l, 48 hr. Component is not readily biodegradable, log Pow: 3-4. Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.. Aquatic Toxicity LC50 96 hr, toxicity rating is <0.10 ppm – extremely toxic

### 13. Waste Disposal

Waste Disposal Method: Dispose of material as a hazardous waste according to federal, state, and local regulations.

### 14. Transport Information

DOT: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, AMINO TERMINATED POLYETHER), 8, PG III

IMO/IMDG : UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, AMINO TERMINATED POLYETHER, NONYL PHENOL), 8, PG III, MARINE POLLUTANT

### 15. Regulatory Information

No data for the product itself.

Component data:

Component CAS# 2855-13-2: Acute health hazard. Ingredients on TSCA. International Chemical status listed/registered – EINECS/ELINCS, DSL, AICS, MITI, TCOL, PICCS, China, New Zealand.

Component Nonyl Phenol: This component is listed on TSCA, EINECS, ACIS, MITI and Canada DSL lists.

Component CAS# 9046-10-0: Target organ effects: Corrosive. Components are on the Massachusetts, Pennsylvania, and New Jersey Right to know lists. Component does not contain chemicals known to California (Prop 65) to cause birth defects or other reproductive harm. This component is listed on TSCA, EINECS, ENCS, AICS, ECL, SEPA, PICCS and Canada DSL lists.

### 16. Disclaimer

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

End of Document