



Freezer Epoxy Mortar Safety Data Sheet

SDS Revision Date: 8/1/2025

1. Product and Company Identification

Product Name Freezer Epoxy Mortar Part A
Product Codes Freezer Epoxy Mortar Part A

Manufacturer Concrete Floor Solutions, Inc.
Street Address 6801 Tilghman Street #113
City, State, Zip Allentown, PA 18106

Information Phone 610-366-0208
Emergency Phone Chemtrec 800-424-9300

Prepared By Jason Kehnel
Date Revised 8/1/2025

Chemical Name or Class Epoxy/Acrylate Mixture

2. Hazards Identification

GHS Classification: Skin corrosion/irritation category 2, serious eye irritation category 2A, skin sensitizer category 1, long term hazards to aquatic environment category 2.

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Aquatic Toxicity



Hazard Statements:

Warning: Causes serious eye irritation.

Warning: Causes skin irritation.

Warning: May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

Precautionary statements:

P102 Keep out of reach of children.
P103 Read label before use P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.
Response P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 IF eye irritation persists: Get medical advice/attention.
P302 + P352 IF ON SKIN: wash with plenty of soap and water.
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.
P362 + P364 take off contaminated clothing and wash it before reuse.
P391 Collect spillage.
P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

HMIS Hazard Classification

Health: 2 Flammability: 1 Reactivity: 1 Personal Protective Equipment: G

Potential Health Effects

Eyes: May cause injury that may persist for several days, redness and tearing may occur.

Skin: May cause irritation or allergic skin response. Reddening or blistering may result from prolonged exposure.

Ingestion: LD50=9.6g/Kg May cause damage to mucous membranes and digestive tract. May cause nausea or other similar responses.

Inhalation: Saturation concentration 0.2mg/L Exposure to heated vapors can cause irritation to the nose, throat, or mucous membranes. At saturation concentration, this material is practically nontoxic.

Health hazards (acute and chronic): Epoxy resins can cause sensitization by exposure through contact or high concentrations of vapor. Eyes - injury is unlikely but stain for evidence of corneal injury. Contains a multi functional monomer that has shown limited evidence of mutagenicity (in vitro.) Health effects can be delayed for 24-48 hours in reference to signs and symptoms of exposure.

Medical conditions generally aggravated by exposure: Respiratory ingredients or other allergic response.

Carcinogenicity

OSHA: No

NTP: Yes

IARC: Yes

Additional carcinogenicity information:

Freezer Epoxy Mortar / SDS Revision Date: 8/1/2025

Some colors may contain carbon black - Explanation Of Carcinogenicity for carbon: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B. Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

3. Composition/Information on Ingredients

Ingredient	Cas No.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Acrylate Inhibited with 100ppm Ether Hydroquinone	15625-89-5	None	None	None	60-100
Reaction Products of Epichlorohydrin-Bisphenol A	25068-38-6	None	None	None	10-30
Titanium Dioxide	13463-67-7	10 mg/m3	10 mg/m3	5 mg/m3	
*CARBON	1333-86-4	3.5 ppm	3.4 ppm	None	<1
Precipitated Silica	112926-00-8	None	80 mg/m3	None	
Iron III oxide	1309-37-1	10 mg/m3	5 mg/m3	None	
Yellow Pigment	Not Available	None	None	None	
Zinc Sulfate (component of yellow pigment)	1314-98-3	None	None	None	
Barium Sulfide (component of yellow pigment)	7727-43-7	None	None	None	
Titanium Dioxide (component of yellow pigment)	13463-67-7	None	None	None	
Pigment yellow 65 (component of yellow pigment)	6528-34-3	None	None	None	
Iron III hydroxide	20344-49-4	15 mg/m3	5 mg/m3	None	
C.I. Pigment Blue	147-14-8	1 mg/m3	1 mg/m3	None	
Aluminum Oxide	1344-28-1	15 mg/m3	10 mg/m3	None	
Silica, amorphous	7631-86-9	80 mg/m3	10 mg/m3	None	

Iron Oxide Yellow	51274-00-1	15 mg/m3	10 mg/m3		
Silica, amorphous	7631-86-9	80 mg/m3	10 mg/m3		

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 Title III and of 40 CFR 372.***

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

4. First Aid Measures

Eyes: Immediately flush eyes with water for 15 minutes and consult a physician.

Skin: Skin contact will normally cause no more than irritation but wash affected areas with soap and water and remove contaminated clothing promptly.

Ingestion: Do not induce vomiting, if large amounts of material are ingested, consult a physician immediately.

Inhalation: Remove to fresh air and administer oxygen if necessary.

5. Fire Fighting Measures

Flammable limits in air	Upper: N/A
(% by volume)	Lower: N/A
Flash point	200+ F
Method used	Seta Flash
Extinguishing media	Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog
Special fire fighting procedures	Do not enter confined fire area without full bunker gear including a positive pressure NIOSH approved self-contained breathing apparatus. Cool all fire exposed containers with water.
Unusual fire and explosion hazards	High temperatures and fire may cause rapid and uncontrolled polymerization which can result in explosion and violent rupture of storage vessels.

6. Release Measures

Steps to be taken in case material is released or spilled - Wear respirator and protective clothing. Shut off the source at the leak. Remove excess with a vacuum truck and take up the remainder with an absorbent such as clay and place in disposal containers. Flush area with water to remove residue.

7. Handling and Storage

Precautions to be taken in handling and storage: Store in a cool dry place. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking, or using toilet facilities.

Mixed materials contain the hazards of all the components, therefore, read the MSDS of all the components prior to using material. Properly label all containers.

Other precautions: Avoid all skin contact. Avoid breathing vapors generated from the material. Observe conditions of good general hygiene and safe working practices. Contaminated leather articles can not be cleaned and must be discarded if contaminated with this product. Wash all contaminated clothing prior to the reuse thereof.

8. Exposure Controls/Personal Protection

Respiratory protection: Use a NIOSH approved respirator as required to prevent over exposure to vapor in accordance with 29 CFR 1910.134. General exhaust is usually sufficient to control vapors and exposure hazards.

Ventilation: General exhaust is usually sufficient to control vapors and exposure hazards.

Protective gloves: Impervious gloves – neoprene or rubber

Eye protection: Splash goggles or glasses with side shields

Other protective clothing or equipment: Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

Work hygienic practices: Observe good general hygienic practices

See Section 3 for occupational exposure limit values

9. Physical and Chemical Properties

Appearance and Odor - Low viscosity liquid - amber clear or colored

Boiling Point or Range - 200+ F

Vapor Density (Air = 1) - N/A

Specific Gravity (H₂O = 1) - 1.0

Evaporation Rate - Not available

Solubility in Water - Negligible

Odor Threshold - N/A

pH - N/A

Melting Point/Freezing Point - N/A

Vapor Pressure - N/A

Auto Ignition Temperature - N/A

Partition Coefficient: n-octanol/water - N/A

Decomposition Temperature- N/A

10. Stability and Reactivity

Stability - Stable

Conditions to Avoid (Stability) - Avoid excessive heat or open flames.

Incompatibility (Material to Avoid) - Can react vigorously with strong oxidizing agents, strong acids or peroxides, copper, iron, rust, and strong bases.

Hazardous Decomposition or By-Products - CO₂, aldehydes, acids. Reaction with some curing agents can generate large amounts of heat.

Hazardous Polymerization - See unusual fire and explosion hazards.

11. Toxicological Information

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD₅₀ >5000 mg/kg (rat), Dermal LD₅₀ >6000 mg/kg (rabbit) COMPONENT Acrylate Inhibited with 100ppm Ether Hydroquinone CAS# 15625-89-5: After Inhalation: No significant signs or symptoms indicative of adverse health hazard are expected to occur at standard conditions due to the low volatility of this material, However, aerosols, or vapors which may be generated at elevated processing temperatures, may cause respiratory tract irritation. Symptoms of irritation may include coughing, mucous production and shortness of breath. After skin contact: No appropriate human or animal health effects data are known to exist. After Eye Contact Although no appropriate human or animal health effects data are known to exist, this material is expected to cause eye irritation. After swallowing: May cause burns, nausea, severe gastroenteritis and vomiting, shock and convulsions. May cause renal damage, as evidenced by bloody urine. LD₅₀ rat > 5000 mg/kg (acrylate) Component Titanium Dioxide: Inhalation 4 h LC₅₀ > 6.82 mg/l; Oral LD₅₀ > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

Component Carbon: IARC lists carbon as a possible human carcinogen Category 2B. LD₅₀ – Intravenous, mouse = 440 mg/kg Component CAS# 112926-00-8: LD₅₀ (rat >5000 mg/kg, LD₅₀ dermal (rat) >2000 mg/kg Component Iron III oxide CAS# 1309-37-1: Acute Oral Toxicity LD₅₀ >5000 mg/kg (rat). Acute Dermal Toxicity LD₅₀ >5000 mg/kg (rat) Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.. Acute oral value of 20 gm/kg or greater in rats Component Iron III hydroxide CAS# 20344-49-4: Acute Oral Toxicity LD₅₀ >5000 mg/kg (rat).

Component CAS# 2210-79-9: Acute Health Hazard -Ingestion : LD₅₀ : 5,800 mg/kg Species : Rat. Inhalation : LC₅₀ (4 h) : 1220 ppm Species : Rat. Skin. : LD₅₀ : > 2,000 mg/kg Species : Rabbit. Method : Estimated. Eye irritation/corrosion : Mild eye irritation Acute dermal irritation/corrosion : Severe skin irritation. Sensitization : May cause sensitization by skin contact.

12. Ecological Information

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l Component Titanium Dioxide: Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50 Component CAS# 112926-00-8: Ecotoxicity: EC50 (fish) .10000 mg/l (daphnia >10000 mg/l Component Iron III oxide CAS# 1309-37-1 Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Acute toxicity to Aquatic Invertebrates EC0 > 10000 mg/l (water flea). Toxicity to Microorganisms EC0 > 1000mg/l (pseudomonas putida) Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200. Component Iron III hydroxide CAS# 20344-49-4: Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Toxicity to Microorganisms EC0 > 10000mg/l (pseudomonas putida)

13. Waste Disposal

Waste Disposal Method: Dispose of material in a waste disposal site in accordance with local, state, and federal law.

14. Transport Information

DOT: Not Regulated

IMO/IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII, Marine Pollutant

15. Regulatory Information

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list,; is on the PA Right to Know List; COMPONENT Acrylate Inhibited with 100ppm Ether Hydroquinone CAS# 15625-89-5: All components of this product are on the TSCA, AICS, Canada DSL, IECSC, EC, ENCS, ECL and PAC inventory list.

Component Titanium Dioxide: Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List.

Titanium Dioxide is in inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN. Component Carbon: Contains Proposition 65 Chemicals .Carbon: is listed on TSCA and DSL Canada Component CAS# 112926-00-8: Is not classified as dangerous. National Chemical Inventory listings include – AICS, DSL, IECSC, EINECS, ENCS, KECI, NZLOC, PICCS, TSCA, Component Iron III oxide CAS# 1309-37-1 Listed on TSCA Inventory. Section 313/312 hazard category: Chronic health hazard. Potential exposure to all of the California proposition 65 have been determined to be below the No significant risk level (NSRL). Component and its impurities (1%) are on the Pennsylvania,

New Jersey right to know substance lists. Component contains the following chemicals listed on the New Jersey and Pennsylvania RTK special hazardous Substance lists: Manganese CAS# 7439-96-5 (0.7%) and Aluminum CAS# 7429-90-5 (0.29%). Component contains the following ingredients which are on the Pennsylvania, Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.075%) and Nickel CAS# 7440-02-0 (0.04%) Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.04%) and Cobalt CAS# 7440-48-4 (30 ppm). Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

Component Iron III hydroxide CAS# 20344-49-4: Listed on TSCA Inventory. Potential exposure to all of the California proposition 65 chemicals have been determined to be below the No significant risk level (NSRL). Components are on the Pennsylvania right to know substance list. Component contains the following chemicals listed on the Pennsylvania RTK special hazardous Substance lists: chromium CAS# 7440-47-3 (0.02%) and nickel CAS# 7440-02-0 (0.015%). Component contains the following ingredients which are on the Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.02%), arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-417 (1ppm) and Nickel CAS# 7440-02-0 (0.015%) Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.015%), arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Cobalt CAS# 7440-48-4 (70ppm)..

Component CAS# 147-14-8: Component is on the TSCA List. and not controlled under WHMIS. Component is a CERCLA hazardous substance Component CAS# 1344-28-1: Component is on the Massachusetts, New Jersey, Pennsylvania right to know lists. Component is on TSCA list and Canada DSL.

Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on TSCA list and Canada DSL.

Component CAS# 51274-00-1: Component is on the TSCA list and Canada DSL.

Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on TSCA list and Canada DSL

16. Other Information

DISCLAIMER: THE INFORMATION HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.

N/A = Not Available

See Section 1 for date of preparation

1. Product and Company Identification

Product Name Freezer Epoxy Mortar Part B
Product Codes Freezer Epoxy Mortar Part B

Manufacturer Concrete Floor Solutions, Inc.
Street Address 6801 Tilghman Street #113
City, State, Zip Allentown, PA 18106

Information Phone 610-366-0208
Emergency Phone Chemtrec 800-424-9300

Prepared By Jason Kehnel
Date Revised 8/1/2025

Chemical Name or Class Polyamine Mixture

2. Hazards Identification

GHS Classification: Specific target organ toxicity single exposure category 3, acute oral toxicity category 4, acute dermal toxicity category 4, serious eye irritation/damage category 1, skin sensitizer category 1B, skin corrosion/irritation category 1, reproductive toxicity category 2, acute hazard to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Health Hazard, Exclamation Mark, Corrosion, Aquatic Toxicity



Hazard Statements:

Warning: May cause respiratory irritation.

Warning: Harmful if swallowed Warning: Harmful in contact with skin Danger: Causes serious eye damage Warning: May cause an allergic skin reaction Danger: Causes severe skin burns and eye damage Warning: Suspected of damaging fertility or the unborn child.

Toxic to aquatic life Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use P261 Avoid breathing dust/fume/gas/mist/vapours/spray P271 Use only outdoors or in a well-ventilated area.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P260 Do not breathe dust/fume/gas/mist/vapours/spray P264 Wash hands thoroughly after handling.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

Response; P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: wash with plenty of soap and water P312 Call a POISON CENTER or doctor/physician if you feel unwell P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 If in eyes, immediately call a POISON CENTER or doctor/physician P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P321 If skin irritation or burns develop, Call a doctor/physician .

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage: P405 Store locked up P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

Other Non-classifiable potential hazards Acute inhalation toxicity category 2 (This product contains a component that is toxic by inhalation and can be fatal if inhaled when aerosolized or sprayed. If the product is not being sprayed or aerosolized, the inhalation toxicity is not applicable. The product is not intended to be sprayed or aerosolized,

HMIS Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Personal Protective Equipment: G

Potential Health Effects

Eyes: Will cause burns to eyes. High vapor concentrations can cause severe irritation to the eyes.

Skin: Will cause burns to the skin.

Ingestion: Liquid can cause severe damage to mucous membranes if swallowed.

Inhalation: High concentrations of vapor can cause irritation to the respiratory tract, nausea, and dizziness.

Health hazards (acute and chronic): Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic responses.

Coal Tar Pitch Emergency Overview: (Danger This product is carcinogenic to humans. Repeated or prolonged contact with skin may cause dermatitis and hyperpigmentation of skin. Avoid breathing dust/fume/gas/mist/vapors and sprays. This product is irritating to the eyes, the skin and the respiratory tract. Exposure to sun may enhance the irritating effect of coal tar pitch on skin and eyes and lead to burns. High vapor concentrations may cause dizziness.

Medical conditions generally aggravated by exposure: Respiratory conditions or other allergic ailments.

Carcinogenicity

OSHA: No

NTP: No

IARC: No

Additional carcinogenicity information:

No listed ingredients of this product are regulated as carcinogens.

3. Composition/Information on Ingredients

Ingredient	Cas No.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Diethylenetriamine	111-40-0	1 ppm	1 ppm	NONE	30-60
*Bisphenol A	80-05-7	NONE	NONE	NONE	10-30
Benzyl Alcohol	100-51-6	NONE	NONE	NONE	30-60

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 Title III and of 40 CFR 372 are present.***

Regulatory standard - NIOSH criteria document, coal tar pitch products. USEPA - 40 CFR 112. (CAS# 65996-93-2 represents the benzene soluble fraction for coal tar pitch volatiles.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

4. First Aid Measures

Eyes: Immediately flush eyes with large amounts of water for at least 15 minutes while lifting upper and lower lids. Get immediate medical assistance.

Skin: Flush skin with water for at least 15 minutes and remove all contaminated clothing immediately. Get medical attention if reddening or swelling occurs.

Ingestion: Do not induce vomiting. Dilute by giving water or milk to drink if the victim is conscious. Get medical attention immediately.

Inhalation: Remove to fresh air and administer oxygen if necessary.

5. Fire Fighting Measures

Flammable limits in air (% by volume)	Upper: N/A Lower: N/A
Flash point	200+ F
Method used	Seta Flash
Extinguishing media	Foam, Alcohol Foam, CO2, Water Fog
Special fire fighting procedures	Toxic fumes will be evolved when this material is involved in a fire. A self-contained breathing apparatus should be available for fire fighting. Cool fire exposed containers with water.
Unusual fire and explosion hazards	None known.

6. Release Measures

Steps to be taken in case material is released or spilled - Avoid contact with material. Wear the appropriate safety equipment. Stop spill at source, dyke area to prevent spreading. Pump liquid to salvage tank. Take up the remainder with clay or other absorbent and place in disposal containers.

7. Handling and Storage

Precautions to be taken in handling and storage: Avoid all skin contact. Avoid breathing vapors. Reseal partially used containers. Properly label all containers. Wash skin areas thoroughly (do not use solvents to wash skin) before eating, drinking, smoking, or using toilet facilities. Observe conditions of good industrial hygiene and safe working practices.

Other precautions: Mixed materials contain the hazards of all the components, therefore, read the MSDS of all components to become familiar with all hazards prior to using this product.

8. Exposure Controls/Personal Protection

Respiratory protection: NIOSH approved respirator protection required in the absence of pepper environmental controls.. For emergencies, a self-contained breathing apparatus or a full face respirator is recommended.

Ventilation: Avoid breathing vapors. Ventilation must be sufficient to control vapors.

Protective gloves: Impervious gloves – neoprene or rubber

Eye protection: Splash goggles or glasses with side shields

Other protective clothing or equipment: Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

Work hygienic practices: Observe good general hygienic practices

See Section 3 for occupational exposure limit values

9. Physical and Chemical Properties

Appearance and Odor - Amber clear liquid with amine odor.

Boiling Point or Range - 155-401 F

Vapor Density (Air = 1) - N/A

Specific Gravity (H₂O = 1) - 1.0

Evaporation Rate - Not available

Solubility in Water - Negligible

Odor Threshold - N/A

pH - N/A

Melting Point/Freezing Point - N/A

Vapor Pressure - N/A

Auto Ignition Temperature - N/A

Partition Coefficient: n-octanol/water - N/A

Decomposition Temperature- N/A

10. Stability and Reactivity

Stability - Stable

Conditions to Avoid (Stability) - Avoid excessive heat or open flames.

Incompatibility (Material to Avoid) - Can react vigorously with strong oxidizing agents and strong lewis acids or mineral acids.

Hazardous Decomposition or By-Products - CO₂, aldehydes, acids. Reaction with some curing agents can generate large amounts of heat.

Hazardous Polymerization - Will not occur

11. Toxicological Information

No data for the product itself.

Component data:

Component CAS# 111-40-0: inhalation: LC₅₀ (4hr) <0.3 mg/l (rat); Skin: LD₅₀ >5000 mg/kg (rabbit) Ingestion: LD₅₀ 2960 mg/kg (rat). Severe Eye irritation, Moderate skin irritation, May cause sensitization by skin contact or inhalation.

Component CAS# 80-05-7: Ingestion LD₅₀ Oral (rat) = 3250 mg/kg. Irritation Data Skin (rabbit) 500 mg/24 hr (mild irritation effects. Irritation data eyes (rabbit) 0.25mg/24 hr (severe irritation effect). Skin contact or inhalation may cause sensitization. Component may impair fertility based on toxicology of similar products.

Component Benzyl Alcohol: Inhalation LC₅₀ (4hr) >4178 mg/l (rat), Dermal LD₅₀ 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse

effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in a two year study with rats and mice.

12. Ecological Information

No data for the product itself.

Component data:

Component CAS# 80-05-7: Acute Ecotoxicity tests LC50 (fathead minnow) 96 hr = 4.6 mg/l.

LC50 (daphnia magna) 48 hr = 3.9 mg/l. LC50 (algae) 96 hr = 2.73 mg/l.

Component Benzyl Alcohol: EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l

Algae, Biodegradation BOD 2 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (*Lepomis macrochirus*), LC50 (96hr) 460 ml/l Fathead minnow (*Pimephales promelas*), Toxicity to Algae: IC50 (72hr) 700 mg/l

13. Waste Disposal

Waste Disposal Method: Dispose of material as a hazardous waste according to federal, state, and local regulations.

14. Transport Information

DOT: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS DIETHYLENETRIAMINE), 8, PG III, MARINE POLLUTANT

IMO/IMDG: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS DIETHYLENETRIAMINE, BISPHENOL A), 8, PG III, MARINE POLLUTANT

15. Regulatory Information

No data for the product itself.

Component data:

Component CAS# 111-40-0: on TSCS List, OSHA hazard class – Irritant. Regulatory List: On TSCA, on EINECS, DSL, AICS, ENCS, ECL, SEPA, PICCS.

Component CAS# 80-05-7: This component is subject to SARA section 313 reporting requirements. Component is on TSCA EINECS, AICS, ENCS, ECL, SEPA, PICCS and Canada DSL lists.

Component Benzyl Alcohol: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

16. Other Information

DISCLAIMER: THE INFORMATION HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA

OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE
ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.

N/A = Not Available

See Section 1 for date of preparation

1. Product and Company Identification

Product Name Freezer Epoxy Mortar Part C
Product Codes Freezer Epoxy Mortar Part C

Manufacturer Concrete Floor Solutions, Inc.
Street Address 6801 Tilghman Street #113
City, State, Zip Allentown, PA 18106

Information Phone 610-366-0208
Emergency Phone Chemtrec 800-424-9300

Prepared By Jason Kehnel
Date Revised 8/1/2025

Chemical Name or Class Sand

2. Hazards Identification

GHS Classification: Carcinogenicity category 1, specific target organ toxicity following repeated exposure category 1, specific target organ toxicity (single exposure) category 3.

GHS Label Elements and Precautionary Statements:

Label Elements: Health Hazard, Exclamation Mark



Hazard Statements:

Hazard Statements:

DANGER: May cause cancer

DANGER: Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system)

WARNING: May cause respiratory irritation.

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray P271 Use only outdoors or in a well-ventilated area.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P405 Store locked up

P403 + P233 Store in a well-ventilated place. Keep the container tightly closed.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

HMIS Hazard Classification

Health: 2 Flammability: 0 Reactivity: 0 Personal Protective Equipment: E

Potential Health Effects

Eyes: May cause reddening of the eyes or eye irritation from airborne particles.

Skin: None known.

Ingestion: None known.

Inhalation: Prolonged exposure to respirable crystalline quartz may cause delayed lung injury (silicosis). Acute or rapidly developing silicosis may occur in a short period of time in heavy exposure in some applications such as sand blasting.

Health hazards (acute and chronic): May cause delayed silicosis or rapid silicosis in some occupations such as sandblasting, silicosis is a form of a disabling pulmonary fibrosis which can be progressive and could lead to death. Inhalation may lead to lung scarring and massive fibrosis which would be accompanied by right heart enlargement, heart failure, or pulmonary failure, smoking aggravates the effects of exposure.

Medical conditions generally aggravated by exposure: Respiratory conditions or other allergic ailments can be aggravated by exposure.

Carcinogenicity

OSHA: No

NTP: Yes

IARC: Yes

Additional carcinogenicity information:

IARC has determined that crystalline silica inhaled in the form of quartz is carcinogenic to humans (group 1- carcinogenic to humans). The NTP classifies respirable crystalline silica as reasonably anticipated to be a carcinogen.

3. Composition/Information on Ingredients

Ingredient	Cas No.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Silicon Dioxide	14808-60-7	0.05 mg/m3	0.025 mg/m3	0.05 mg/m3	100

*No toxic chemical(s) subject to the reporting requirements of section 313 Title III and of 40 CFR 372 are present.***

Follow OSHA hazard communication rule 29 CFR sections 1910.1200, 1915.99, 1917.28, 1918.9, 1926.59, and state and local community right to know laws. We recommend that smoking be prohibited in areas where respirators must be used.

4. First Aid Measures

Eyes: Flush eyes with water for at least 15 minutes and consult a physician if conditions warrant.

Skin: Skin contact will normally cause no health risks.

Ingestion: If ingested, consult a physician.

Inhalation: Remove to fresh air and administer oxygen if necessary.

5. Fire Fighting Measures

Flammable limits in air Upper: N/A

(% by volume) Lower: N/A

Flash point N/A

Method used N/A

Extinguishing media Other

Special fire fighting procedures Crystalline silica is neither a fire nor an explosion hazard.

Unusual fire and explosion hazards None known.

6. Release Measures

Steps to be taken in case material is released or spilled - Wear a respirator and use dustless handling equipment to clean up large spills. Place in suitable containers for disposal. Flush area with water after pickup of material.

7. Handling and Storage

Precautions to be taken in handling and storage: Store in a cool dry place. Properly label all partially used containers. Avoid creating any dust when working with this material.

Other precautions: Avoid breathing dust generated from the material. Observe conditions of good general hygiene and safe working practices. Provide training for your employees relating to occupational exposure to quartz dust. See ASTM standard E1132-86 standard practice for health requirements relating to exposure to quartz dust. If better than 500 X PEL use a self contained breathing apparatus. If sandblasting, use any type CE supplied air respirator with full face piece or hood.

Safety phrases

S22 Do not breathe dust

S25 Avoid contact with eyes

S38 In case of insufficient ventilation wear suitable respiratory equipment

S39 Wear eye/face protection

8. Exposure Controls/Personal Protection

Respiratory protection: Use a NIOSH approved respirator as required to prevent over exposure to quartz dust. Provide sufficient exhaust to keep exposure levels below the ACGIH PEL.

Ventilation: Use exhaust sufficient to maintain airborne particulates below the ACGIH PEL limits established.

Protective gloves: N/A

Eye protection: Splash goggles or glasses with side shields

Other protective clothing or equipment: Provide any equipment necessary to prevent inhalation of quartz dust.

Work hygienic practices: Observe good general hygienic practices

See Section 3 for occupational exposure limit values

9. Physical and Chemical Properties

Appearance and Odor - White tan sand granular crushed or ground - no odor

Boiling Point or Range - N/A

Vapor Density (Air = 1) - N/A

Specific Gravity (H₂O = 1) - 2.6

Evaporation Rate - Not available

Solubility in Water - Insoluble in water

Odor Threshold - N/A

pH - N/A

Melting Point/Freezing Point - N/A

Vapor Pressure - N/A

Auto Ignition Temperature - N/A

Partition Coefficient: n-octanol/water - N/A

Decomposition Temperature- N/A

10.Stability and Reactivity

Stability - Stable

Conditions to Avoid (Stability) - Contact with powerful oxidizing agents such as fluorine, chlorine, trifluoride, manganese trioxide, oxygen trifluoride.

Incompatibility (Material to Avoid) - Can react vigorously with strong oxidizing agents. See conditions to avoid.

Hazardous Decomposition or By-Products - Silica will dissolve in hydrochloric acid to form a corrosive gas-silicon tetrafluoride.

Hazardous Polymerization - Will not occur

11. Toxicological Information

Silicon dioxide: Inhalation and retention of respirable crystalline silica can cause silicosis in several forms, chronic, accelerated or acute. Acute silicosis can occur with exposures to high concentrations of respirable crystalline silica over a very short time period, the symptoms of acute silicosis include progressive shortness of breath, fever, cough, and weight loss. Acute silicosis can be fatal. IARC concluded that there was sufficient evidence in humans for the carcinogenicity of crystalline silica in the form of quartz (Group 1). Exposure to respirable crystalline silica can also be associated with autoimmune disease, tuberculosis, kidney damage, and non-malignant respiratory disease. For further information, the NIOSH Hazard Review- Occupational Effects of Occupational Exposure to Respirable Crystalline Silica published in April of 2002 should be reviewed.

12.Ecological Information

Silicon Dioxide: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

13.Waste Disposal

Waste Disposal Method: DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

14.Transport Information

DOT: Not Regulated

IMO/IMDG: Not Regulated

15.Regulatory Information

Silicon Dioxide: risk phrases: R 48/20 Harmful – Danger of serious damage to health by prolonged exposure through inhalation. Safety Phrases: S 22 – Do not breathe dust and S 38 – In case of insufficient ventilation, wear suitable respiratory equipment

Crystalline Silica (Silicon Dioxide) is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

Crystalline Silica (Silicon Dioxide) is on the Canada DSL – WHMIS Classification D2A
Crystalline Silica is on the Australian Inventory of Chemicals Substances list, Japan Ministry of International Trade and Industry list, Korea Existing Chemicals Inventory with registry number 9212-5667 and the Philippines Inventory of Chemicals and Chemical Substances list.

16. Other Information

DISCLAIMER: THE INFORMATION HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.

N/A = Not Available

See Section 1 for date of preparation

End of Document