



## CONCRETE FLOOR SOLUTIONS FLOOR MAINTENANCE GUIDE

### **TIPS: EXTENDING THE LIFE OF EPOXY&POLYASPARTIC FLOORING**

- Clean spills including food and beverages, grease, oil, chemicals, salts and other contaminants immediately. Leaving spills can cause the floor to discolor and some chemicals may even cause the floor to soften or peel.
- Ensure wheels on equipment such as fork trucks and hand trucks are maintained, especially steel wheels that can cause scratches and marks.
- Clean the floor regularly by mopping with a mild soap solution as needed. Always test any cleaners prior to use. Rinse the floor completely after cleaning to be sure no soapy residue is left behind.
- For heavily soiled areas, a floor scrubber with soft bristles may be used.
- Avoid use of stiff bristle brushes that can dull out the floor.
- Ensure good housekeeping by sweeping the floor to remove abrasives, dirt, and other materials that can scratch or mark the floor.
- Take care not to drop or drag heavy, sharp objects on the floor (including pallets). Carry or use a hand truck when transporting boxes, pallets or other objects.
- Place pads on the legs of chairs, tables and other furniture to prevent markings on the floor.
- Do not use any cleaners or paint strippers that contain solvent or Methylene Chloride. This chemical is designed to remove epoxies and urethanes.